

Safety data sheet
according to P.U.(A) 310/2013

Printing date 23.10.2017

Version number 2

Revision: 23.10.2017

1 Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name **weber set x'tra flex (LD) (grey & white)**

Safety data sheet no.: XXP014108

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Tile adhesive

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint-Gobain Weber (M) Sdn Bhd

No. 29&31, Jalan TIAJ 2/1, Taman Industri Alam Jaya, 42300 Bandar Puncak Alam, Selangor D E

Tel: +603-60389094/9084 Fax: +603-60389507

Emergency telephone number: Tel.: +603-60389094/9084

2 Hazards identification

Classification of the substance or mixture



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Label elements

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

cement portland, grey

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)

Safety data sheet

according to P.U.(A) 310/2013

Printing date 23.10.2017

Version number 2

Revision: 23.10.2017

Trade name weberset x'tra flex (LD) (grey & white)


(Contd. of page 1)

P103 Read label before use.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P321 Specific treatment (see on this label).
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards**Results of PBT and vPvB assessment****PBT:** Does not contain PBT substances.**vPvB:** Does not contain vPvB substances.

3 Composition/information on ingredients

Chemical characterisation: Mixtures**Description:** Mixture of substances listed below with non hazardous additions.

Dangerous components:		
65997-15-1	cement portland, grey 	25-50%
471-34-1	calcium carbonate	2-5%

SVHC Void**Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

Description of first aid measures**General information**

Immediately remove any clothing soiled by the product.

Remove the victim immediately from the danger area. If the patient is unwell consult a doctor and present this data sheet.

After inhalation Supply fresh air and to be sure call for a doctor.**After skin contact** Immediately rinse with water.**After eye contact**

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

Information for doctor**Most important symptoms and effects, both acute and delayed**

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

MY2

(Contd. on page 3)

Safety data sheet

according to P.U.(A) 310/2013

Printing date 23.10.2017

Version number 2

Revision: 23.10.2017

Trade name weberset x'tra flex (LD) (grey & white)

(Contd. of page 2)

5 Firefighting measures

Extinguishing media
Suitable extinguishing agents The product is not combustible.

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters
Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Ensure adequate ventilation.

Environmental precautions: No special measures required.

Methods and material for containment and cleaning up:

Use neutralising agent.

Pick up mechanically.

Ensure adequate ventilation.

Dispose of contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling
Precautions for safe handling

Keep receptacles tightly sealed.

Prevent formation of dust.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

MY2

Safety data sheet

according to P.U.(A) 310/2013

Printing date 23.10.2017

Version number 2

Revision: 23.10.2017

Trade name weberset x'tra flex (LD) (grey & white)

(Contd. of page 3)

Control parameters**Ingredients with limit values that require monitoring at the workplace:**

CAS No.	Designation of material	%	Type	Value	Unit
65997-15-1 cement portland, grey					
PEL (Malaysia)	Long-term value: 10 mg/m ³				
PEL (USA)	Long-term value: 50 mppcf or 15* 5** mg/m ³ *total dust **respirable fraction				
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction				
TLV (USA)	Long-term value: 1* mg/m ³ E; *as respirable fraction				
471-34-1 calcium carbonate					
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction				
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction				
TLV (USA)	TLV withdrawn				

Additional Occupational Exposure Limit Values for possible hazards during processing:total inhalable dust: 10 mg/m³alveolar dust (< 5 µm): 4 mg/m³Quartz alveolar dust (< 5 µm) : 0,15 mg/m³**Additional information:**

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter P2.

Protection of hands: Protective gloves.

Material of gloves Nitrile impregnated cotton gloves complying with the standard EN 374-1.

Eye protection: Tightly sealed goggles

Body protection: Protective work clothing.

MY2

(Contd. on page 5)

Safety data sheet

according to P.U.(A) 310/2013

Printing date 23.10.2017

Version number 2

Revision: 23.10.2017

Trade name weberset x'tra flex (LD) (grey & white)

(Contd. of page 4)

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:	Solid.
Colour:	Grey
Odour:	Odourless
Odour threshold:	Not determined.

pH-value:	Alkaline
-----------	----------

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Not applicable

Flash point:	Not applicable
--------------	----------------

Flammability (solid, gas):	Product is not flammable.
----------------------------	---------------------------

Ignition temperature:	Not determined.
-----------------------	-----------------

Decomposition temperature:	Not determined.
----------------------------	-----------------

Auto-ignition temperature:	Product is not selfigniting.
----------------------------	------------------------------

Explosive properties:	Product does not present an explosion hazard.
-----------------------	---

Explosion limits:

Lower:	Not applicable
Upper:	Not applicable
Oxidising properties	Not determined.

Vapour pressure:	Not applicable.
------------------	-----------------

Density:	1,72g/cm ³
----------	-----------------------

Bulk density:	Not determined.
Relative density	Not determined.
Vapour density	Not applicable.
Evaporation rate	Not applicable.

Solubility in / Miscibility with

Water:	Hardens when in contact with water.
--------	-------------------------------------

Segregation coefficient (n-octanol/water) log

Pow:	Not determined.
------	-----------------

Viscosity:

dynamic:	Not applicable.
kinematic:	Not applicable.

Solvent content:

Organic solvents:	0,0%
EU-VOC	0.00 %
Solids content:	100%
Other information	None.

MY2

(Contd. on page 6)

Safety data sheet

according to P.U.(A) 310/2013

Printing date 23.10.2017

Version number 2

Revision: 23.10.2017

Trade name weberset x'tra flex (LD) (grey & white)

(Contd. of page 5)

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions

Reacts with acids

Reacts with light alloys in the presence of moisture to form hydrogen

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:

Components	Type	Value	Species
65997-15-1 cement portland, grey			
Dermal	LD50	>2,000 mg/kg	(Rabbit)

Primary irritant effect:

Skin corrosion/irritation Irritant to skin and mucous membranes.

Serious eye damage/irritation Strong irritant with the danger of severe eye injury.

Respiratory or skin sensitisation Sensitisation possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behaviour in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark:

The product contains substances which causes severe clouding in water

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Remark: The product causes a significant pH change. Neutralise before introduction.

(Contd. on page 7)

MY2

Safety data sheet

according to P.U.(A) 310/2013

Printing date 23.10.2017

Version number 2

Revision: 23.10.2017

Trade name weberset x'tra flex (LD) (grey & white)

(Contd. of page 6)

Additional ecological information:**General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods**Recommendation**

Product hardens after adding water after 5 to 6 hours and can then be disposed of as building rubbish. Possible waste code 17 09 04.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent:

Water, if necessary together with cleansing agents.

Thoroughly shake out sacks.

14 Transport information

UN-Number ADR, ADN, IMDG, IATA	Void
UN proper shipping name ADR, ADN, IMDG, IATA	Void
Transport hazard class(es) ADR, ADN, IMDG, IATA Class	Void
Packing group ADR, IMDG, IATA	Void
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

MY2

(Contd. on page 8)

Safety data sheet

according to P.U.(A) 310/2013

Printing date 23.10.2017

Version number 2

Revision: 23.10.2017

Trade name weberset x'tra flex (LD) (grey & white)

(Contd. of page 7)

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

cement portland, grey

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Research and Development

Contact:

Teh Kim Heok, +603-60389094/9084

KimHeok.Teh@saint-gobain.com

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 9)

-MY2

Safety data sheet
according to P.U.(A) 310/2013

Printing date 23.10.2017

Version number 2

Revision: 23.10.2017

Trade name weberset x'tra flex (LD) (grey & white)

(Contd. of page 8)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

*** Data compared to the previous version altered.**

MY2